

## DGK115/HB/KG

H2GO D400 kerb unit 440mm x 305mm clear opening with 150mm frame depth



RANGE	CLEAR OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)	OPTIONS
H2GO	440 x 305	645 x 445	150	<input type="checkbox"/> Ventilation holes

## KEY FEATURES

- ✓ Reversible hinge allows the grating to hinge with the direction of the traffic flow, improving safety.
- ✓ Mechanical lifting points are provided.
- ✓ Captive hinges reduce theft risk whilst allowing easy lifting.
- ✓ Safety keyway prevents accidental disengagement of the lifting key during the handling process.

## SPECIFICATION

### General information

Stock code	DGK115/HB/KG
Primary material	Ductile iron
Range	H2GO
Category	Kerb unit
Flanges	4

## Standards, classes and groupings

Standards	BS EN 124-2 CD 534 (formerly HA 104/09)
BS EN 124 Class	D400
BS EN 124 Group	3
Third party certified	Kitemark

## Dimensions

Frame shape	Rectangular
Overall frame (A x B)	645 mm x 445 mm
Clear opening (C x D)	440 mm x 305 mm
Frame depth (E)	150mm
Base opening (F x G)	530 mm x 370 mm
Waterway area	88.7cm <sup>2</sup>

## AVAILABLE OPTIONS

### ✓ Ventilation holes

Provide additional cover ventilation in addition to the product's natural ventilation, up to the BS EN 124 allowance.

## ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm

STOCK CODE	DESCRIPTION
YPCR/U12.5	12.5Kg Unipak® rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak® rapid curing polyester resin mortar
SCREWLIFT	Manhole cover levelling system
GRITBLOCKER	Anti-blockage keyway insert
KEY/LONG	Large cover lifting keys with a long handle (sold as a pair)
KEYSHEAVY	Large cover lifting keys with a standard handle (sold as a pair)
KEYS/L	Small cover combined lifting key

## NOTES

## Compatible with

Stock code	Description
<a href="#">DGCC/6545/G</a>	H2GO gully chute connector 655mm x 450mm x 185mm with 150mm and 160mm spigot sizes

All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

